

AzureResponsesModel

September 4, 2026

AzureResponsesModel

Kind: Class**Source:** [atloria-monorepo/libs/agent-core/src/runtime/model-adapter.ts](https://github.com/atloria-monorepo/libs/agent-core/src/runtime/model-adapter.ts)

Azure OpenAI Model — implements the SDK's Model interface using Azure Responses API.

Implements: `Model`

Methods

Method	Signature	Returns
<code>getResponse</code>	<code>getResponse(request: ModelRequest)</code>	<code>Promise<ModelResponse></code>
<code>getStreamedResponse</code>	<code>getStreamedResponse(request: ModelRequest)</code>	<code>AsyncIterable<import('@openai/agents').ResponseStreamEvent></code>
<code>getRetryAdvice</code>	<code>getRetryAdvice(args: ModelRetryAdviceRequest)</code>	<code>`ModelRetryAdvice</code>

Where it refuses work

- `AzureResponsesModel` stops the work with an early return when `!event?.type` .
- `AzureResponsesModel` stops the work with an early return when `!usage` .
- `AzureResponsesModel` stops the work with an early return when `!Array.isArray(output)` .
- `AzureResponsesModel` stops the work with an early return when `!item || typeof item !== 'object'` .
- `AzureResponsesModel` stops the work with an early return when `message.includes('429') || message.includes('throttled')` .
- `AzureResponsesModel` stops the work with an early return when `message.includes('500') || message.includes('502') || message.includes('503')` .

When something fails

- `AzureResponsesModel` handles failure in 4 places: it lets it reach the caller in 2, turns it into a return value in 1, and discards it silently in 1. A failure discarded silently leaves no trace for whoever debugs this later.