

MarkdownParser

September 4, 2026

MarkdownParser

Kind: Class

Source: [atloria-monorepo/apps/config-docs-parser/src/parsers/markdown.parser.ts](https://github.com/atloria-monorepo/apps/config-docs-parser/src/parsers/markdown.parser.ts)

Implements: `IParser`

Methods

Method	Signature	Returns
<code>initialize</code>	<code>initialize(config: ParserConfig)</code>	<code>Promise<void></code>
<code>canParse</code>	<code>canParse(filePath: string)</code>	<code>boolean</code>
<code>parseFile</code>	<code>parseFile(filePath: string, content: string)</code>	<code>Promise<ParseResult></code>
<code>parseFiles</code>	<code>parseFiles(files: ParseFileInput[])</code>	<code>Promise<ParseResult[]></code>
<code>destroy</code>	<code>destroy()</code>	<code>Promise<void></code>

Properties

Property	Type
<code>name</code>	<code>any</code>
<code>version</code>	<code>any</code>
<code>supportedPatterns</code>	<code>any</code>

Where it refuses work

- `MarkdownParser` stops the work with `Error` when `!content` — “Content is required for parsing”.
- `MarkdownParser` stops the work with an early return when `typeMap[baseName]`.
- `MarkdownParser` stops the work with an early return when `/guide/i.test(fileName)`.

- `MarkdownParser` stops the work with an early return when `/tutorial/i.test(fileName)` .
- `MarkdownParser` stops the work with an early return when `/api/i.test(fileName)` .
- `MarkdownParser` stops the work with an early return when `/docs?/i.test(filePath)` .

When something fails

- `MarkdownParser` handles failure in 1 place: it turns it into a return value in all 1.