

OpenAPIParser

September 4, 2026

OpenAPIParser

Kind: Class

Source: [atloria-monorepo/apps/api-schema-parser/src/parsers/openapi.parser.ts](https://github.com/atloria-monorepo/apps/api-schema-parser/src/parsers/openapi.parser.ts)

OpenAPI Parser Implementation

Supports:

- OpenAPI 3.0.x and 3.1.x
- Swagger 2.0
- JSON and YAML formats

Implements: `IParser`

Methods

Method	Signature	Returns
<code>initialize</code>	<code>initialize(config: ParserConfig)</code>	<code>Promise<void></code>
<code>canParse</code>	<code>canParse(filePath: string)</code>	<code>boolean</code>
<code>parseFile</code>	<code>parseFile(filePath: string, content: string)</code>	<code>Promise<ParseResult></code>
<code>parseFiles</code>	<code>parseFiles(files: ParseFileInput[])</code>	<code>Promise<ParseResult[]></code>
<code>destroy</code>	<code>destroy()</code>	<code>Promise<void></code>

Properties

Property	Type
<code>name</code>	<code>any</code>
<code>version</code>	<code>any</code>
<code>supportedPatterns</code>	<code>any</code>

Where it refuses work

- `OpenAPIParser` stops the work with an early return when `!pathItem` , in 4 places.
- `OpenAPIParser` stops the work with an early return when `!operation` , in 4 places.
- `OpenAPIParser` stops the work with an early return when `schema.type === 'array' && schema.items` .
- `OpenAPIParser` stops the work with an early return when `!schema` .
- `OpenAPIParser` stops the work with an early return when `ref` .
- `OpenAPIParser` stops the work with an early return when `!requestBody` .

When something fails

- `OpenAPIParser` handles failure in 2 places: it logs it and continues in 1, and turns it into a return value in 1.