

JSXFragmentNode

August 17, 2026

JSXFragmentNode

Kind: Class**Source:** `src/jsx/base.ts`**Part of:** `Jsx`

`JSXFragmentNode` represents a JSX fragment node within the JSX node model. Its `toStringToBuffer()` method writes the fragment's string form to the active output buffer instead of returning a string.

Extends: `JSXNode`

Methods

Method	Signature	Returns
<code>toStringToBuffer</code>	<code>toStringToBuffer(buffer: StringBufferWithCallbacks)</code>	<code>void</code>

Diagram

```
graph LR
    Fragment[JSXFragmentNode] --> Writer[toStringToBuffer()]
    Writer --> Buffer[Output Buffer]
```

Usage

```
import { JSXFragmentNode } from "../jsx/base";

function writeFragment(fragment: JSXFragmentNode): void {
    fragment.toStringToBuffer();
}
```

AI Coding Instructions

- Call `toStringToBuffer()` when rendering a fragment through the buffer-based output path.
- Do not expect `toStringToBuffer()` to return rendered content; it returns `void`.
- Keep fragment rendering consistent with other JSX node types in `src/jsx/base.ts`.
- Pass `JSXFragmentNode` instances through code that manages the active output buffer.

Used by

1 reference from 1 file. Each is a place in this repository where the symbol is actually used — go read one rather than trusting an example.

Imported by (1)

- `Context` — `src/jsx/context.ts :8`