

defaultPlugin

August 17, 2026

defaultPlugin

Kind: Function

Source: `src/helper/ssg/plugins.ts`

Part of: [Helper](#)

The default plugin that defines the recommended behavior.

`defaultPlugin` creates the plugin that applies the project's recommended static-site-generation behavior. Add it to the SSG plugin list so its hooks participate in the build lifecycle.

Signature

```
function defaultPlugin(): SSGPlugin
```

Returns: `SSGPlugin`

Diagram

```
graph LR
    Config[SSG configuration] --> PluginFactory[PluginFactory[defaultPlugin()]]
    PluginFactory --> Plugin[Plugin[Default plugin]]
    Plugin --> Build[SSG build lifecycle]
    Build --> Output[Generated site output]
```

Usage

```
import { defaultPlugin } from './src/helper/ssg/plugins';

const plugins = [
  defaultPlugin(),
];
```

```
export { plugins };
```

AI Coding Instructions

- Keep `defaultPlugin()` in the SSG plugin configuration so the default build behavior remains active.
- Follow the plugin hook and return-value conventions already used in `src/helper/ssg/plugins.ts`.
- Avoid duplicating behavior implemented by the default plugin in custom plugins.
- When changing plugin behavior, verify how the change affects generated static output and build-time hooks.

Relationships

- IMPORTS → `html`

Used by

1 reference from 1 file. Each is a place in this repository where the symbol is actually used — go read one rather than trusting an example.

Imported by (1)

- `DEFAULT_OUTPUT_DIR` — `src/helper/ssg/ssg.ts` :27