



MIDDLEWARE

detectFromPath

Kind: Function

VERSION
5

UPDATED
12 August 2026

DOCUMENT
reference-subsystem-src-middleware/function-detectfrompath

CONTENTS

1	Signature	2	4	Usage	3
2	Parameters	2	5	AI Coding Instructions	3
3	Diagram	2			

Kind: Function

Source: `src/middleware/language/language.ts`

Part of: [Middleware](#)

Detects language from URL path

`detectFromPath` reads a URL path and determines the language encoded in that path. It is used by the language middleware to select the request language before downstream handlers process the request.

1 Signature


```
function detectFromPath(c: Context, options: DetectorOptions): string | undefined
```

2 Parameters

Name	Type
<code>c</code>	<code>Context</code>
<code>options</code>	<code>DetectorOptions</code>

Returns: `string | undefined`

3 Diagram



4 Usage

```
import { detectFromPath } from './middleware/language/language';

const language = detectFromPath('/en/docs/getting-started');

if (language) {
  console.log(`Detected language: ${language}`);
}
```

5 AI Coding Instructions

- Pass the URL pathname rather than the full URL when calling `detectFromPath`.
- Keep path parsing rules consistent with the language prefixes supported by the middleware.
- Handle cases where no language is detected before selecting localized content.
- Update related routing and middleware behavior when changing language path formats.