

parseAcceptLanguage

August 17, 2026

parseAcceptLanguage

Kind: Function

Source: `src/middleware/language/language.ts`

Part of: [Middleware](#)

Parse Accept-Language header values with quality scores

`parseAcceptLanguage` parses an `Accept-Language` header into language preferences and accounts for quality-score parameters. It is used by language middleware to determine the client's preferred language order before locale selection.

Signature

```
function parseAcceptLanguage(header: string): Array<{ lang: string; q: number }>
```

Parameters

Name	Type
<code>header</code>	<code>string</code>

Returns: `Array<{ lang: string; q: number }>`

Diagram

```
graph LR
  Header[Accept-Language header] --> Parse[parseAcceptLanguage]
  Parse --> Entries[Language entries with quality scores]
  Entries --> Ordered[Preferred language order]
  Ordered --> Middleware[Language middleware]
```

Usage

```
import { parseAcceptLanguage } from "../middleware/language/language";

const header = request.headers.get("accept-language") ?? "";
const preferredLanguages = parseAcceptLanguage(header);

// Pass the parsed preferences to locale-selection logic.
const locale = selectSupportedLocale(preferredLanguages);
```

AI Coding Instructions

- Keep parsing aligned with the `Accept-Language` header format: comma-separated language ranges with optional quality parameters.
- Preserve quality-score ordering when changing parsing logic, since downstream locale selection depends on preference order.
- Handle missing or empty header values before calling the function when integrating with request middleware.
- Keep locale matching separate from header parsing; this function should only interpret client preferences.