

poweredBy

August 17, 2026

poweredBy

Kind: Function**Source:** `src/middleware/powered-by/index.ts`**Part of:** Middleware

Powered By Middleware for Hono.

`poweredBy` creates Hono middleware that adds an `X-Powered-By` response header. It runs after downstream middleware and handlers, allowing the header value to be configured with `serverName`.

Signature

```
function poweredBy(options: PoweredByOptions): MiddlewareHandler
```

Parameters

Name	Type
<code>options</code>	<code>PoweredByOptions</code>

Returns: `MiddlewareHandler`

Diagram

```
graph LR
  A[Incoming request] --> B[poweredBy middleware]
  B --> C[Downstream middleware and route handler]
  C --> D[Set X-Powered-By response header]
  D --> E[Response]
```

Usage

```
import { Hono } from 'hono'
import { poweredBy } from 'hono/powered-by'

const app = new Hono()

app.use('*', poweredBy({ serverName: 'My API' }))

app.get('/', (c) => {
  return c.text('Hello')
})

export default app
```

AI Coding Instructions

- Register `poweredBy()` with `app.use()` so it applies to the intended routes.
- Pass `serverName` when the default `Hono` header value should be replaced.
- Keep `await next()` in the middleware flow so downstream handlers run before the response header is set.
- Check for other middleware that sets `X-Powered-By` , since later header writes can replace earlier values.