



PAMS

GetbyParentFileID_old

Kind: API Endpoint

VERSION
4

UPDATED
11 August 2026

DOCUMENT
reference-subsystem-pams/api-endpoint-getbyparentfileid-old

CONTENTS

1	Endpoint	2	2	Used by	2
---	----------	---	---	---------	---

Kind: API Endpoint

Source: `Pams/API/Pams.API/Controllers/Common/FilesController.cs` (line 121)

Part of: [Pams](#)

1 Endpoint

GET

Parameter	In	Type	Required	Description
<code>branchId</code>	query	<code>long</code>	✓	
<code>userId</code>	query	<code>long</code>	✓	
<code>allowedBranches</code>	query	<code>string</code>	✓	
<code>parentFileId</code>	query	<code>long</code>	-	
<code>startRecord</code>	query	<code>int</code>	-	
<code>pageSize</code>	query	<code>int</code>	-	
<code>filterObject</code>	query	<code>string</code>	-	
<code>order</code>	query	<code>int</code>	-	
<code>orderType</code>	query	<code>string</code>	-	
<code>customstore</code>	query	<code>int</code>	-	

2 Used by

1 reference from 1 file. Each is a place in this repository where the symbol is actually used — go read one rather than trusting an example.

Declared in (1)

- `FilesController` — `Pams/API/Pams.API/Controllers/Common/FilesController.cs`:27