PAMS

Insert

Kind: API Endpoint

VERSION	UPDATED	DOCUMENT
4	11 August 2026	reference-subsystem-pams/api-endpoint-insert-18

CONTENTS

1 Endpoint 2
2 Used by 2

Kind: API Endpoint

Source: `Pams/API/Pams.API/Controllers/Common/ReactivationReasonsController.cs` (line 55)

Part of: Pams

1 Endpoint

`POST`

2 Used by

27 references from 27 files. Each is a place in this repository where the symbol is actually used — go read one rather than trusting an example.

Declared in (1)

- `ReactivationReasonsController` — `Pams/API/Pams.API/Controllers/Common/ReactivationReasonsController.cs`:15

Imported by (26)

- `AddressController` — `Pams/API/Pams.API/Controllers/Common/AddressController.cs`:15
- `CityController` — `Pams/API/Pams.API/Controllers/Common/CityController.cs`:20
- `CompanyBranchContactInfoController` — `Pams/API/Pams.API/Controllers/Organization/CompanyBranchContactInfoController.cs`:18
- `ConnectionTypeController` — `Pams/API/Pams.API/Controllers/Common/ConnectionTypeController.cs`:16
- `ContactInfoController` — `Pams/API/Pams.API/Controllers/Common/ContactInfoController.cs`:15
- `ContactInfoRelatedTypeController` — `Pams/API/Pams.API/Controllers/Common/ContactInfoRelatedTypeController.cs`:15
- `ContactInfoTypeController` — `Pams/API/Pams.API/Controllers/Common/ContactInfoTypesController.cs`:19
- `ContactPersonController` — `Pams/API/Pams.API/Controllers/Common/ContactPersonController.cs`:17

...and 18 more.