

NewJobService

August 17, 2026

NewJobService

Kind: Class**Source:** Pams/Web/Pams.Web/Client/app/services/sales/new-job/new-job.service.ts (line 16)**Part of:** Pams

`NewJobService` coordinates data and actions for sales new-job workflows. It retrieves branch, sales responsible, product type, time-frame, and status data sources, then handles job save, update, and inquiry deletion operations.

Methods

Method	Signature	Returns
<code>getCurrentBranch</code>	<code>getCurrentBranch()</code>	<code>void</code>
<code>getSalesResponsiblesDataSource</code>	<code>getSalesResponsiblesDataSource(companyBranchForData: number)</code>	<code>void</code>
<code>getSalesResponsiblesDataSourceWithEnum</code>	<code>getSalesResponsiblesDataSourceWithEnum(departmentIdEnum: number, companyBranchForData: number)</code>	<code>void</code>
<code>getProductTypesDataSource</code>	<code>getProductTypesDataSource()</code>	<code>void</code>
<code>getPurchasingProductTypesDataSource</code>	<code>getPurchasingProductTypesDataSource()</code>	<code>void</code>
<code>getTimeFramePeriodsDataSource</code>	<code>getTimeFramePeriodsDataSource()</code>	<code>void</code>
<code>getStatusDataSource</code>	<code>getStatusDataSource(stage: undefined)</code>	<code>void</code>
<code>saveJob</code>	<code>saveJob(job: undefined)</code>	<code>void</code>
<code>updateJob</code>	<code>updateJob(job: undefined)</code>	<code>void</code>
<code>deleteInquiry</code>	<code>deleteInquiry(id: undefined)</code>	<code>void</code>
<code>getsalesjobbyid</code>	<code>getsalesjobbyid(id: undefined)</code>	<code>void</code>
<code>getDeliveriesForInstandSalesJob</code>	<code>getDeliveriesForInstandSalesJob(Jobid: undefined)</code>	<code>void</code>
<code>createInquiry</code>	<code>createInquiry(inquiry: undefined)</code>	<code>void</code>
<code>updateInquiry</code>	<code>updateInquiry(inquiry: undefined)</code>	<code>void</code>
<code>deleteJob</code>	<code>deleteJob(id: undefined)</code>	<code>void</code>
<code>changeJobStatus</code>	<code>changeJobStatus(job: undefined)</code>	<code>void</code>

Method	Signature	Returns
regretJob	regretJob(id: undefined, regretDetails: undefined)	void
unRegretPotentialJob	unRegretPotentialJob(id: undefined)	void
cancelJob	cancelJob(id: undefined, cancelDetails: undefined)	void
unCancelPotentialJob	unCancelPotentialJob(id: undefined)	void
convertJobToOffer	convertJobToOffer(id: undefined)	void
regretOfferedJob	regretOfferedJob(id: undefined, regretDetails: undefined)	void
unRegretOfferedJob	unRegretOfferedJob(id: undefined)	void
cancelOfferedJob	cancelOfferedJob(id: undefined, cancelDetails: undefined)	void
unCancelOfferedJob	unCancelOfferedJob(id: undefined)	void
convertJobToPotential	convertJobToPotential(id: undefined)	void
lostOfferedJob	lostOfferedJob(id: number, lossDetails: undefined)	void
unLossOfferedJob	unLossOfferedJob(id: number)	void
unRejectOrderedJob	unRejectOrderedJob(id: number)	void
createSingleOffer	createSingleOffer(offer: SalesOffers)	void
approveOfferArchiveRequest	approveOfferArchiveRequest(offerId: number)	void
disapproveOfferArchiveRequest	disapproveOfferArchiveRequest(offerId: number)	void
changeStageSingleOffer	changeStageSingleOffer(offer: SalesOffers)	void
updateSingleOffer	updateSingleOffer(offer: SalesOffers)	void
regretSingleOffer	regretSingleOffer(id: number, regretDetails: undefined)	void
getregrettedOfferReason	getregrettedOfferReason(archivedId: number)	void
updateRegrettedOfferReason	updateRegrettedOfferReason(Id: number, regretDetails: RegretReasonModel)	void
unRegretSingleOffer	unRegretSingleOffer(id: number)	void
cancelSingleOffer	cancelSingleOffer(id: number, cancelDetails: undefined)	void
getCancelledOfferReason	getCancelledOfferReason(archivedId: number)	void
updateCancelledOfferReason	updateCancelledOfferReason(Id: number, cancelDetails: CancelReasonModel)	void
unCancelSingleOffer	unCancelSingleOffer(id: number)	void
lostSingleOffer	lostSingleOffer(id: number, lostDetails: undefined)	void
getLostOfferReason	getLostOfferReason(archivedId: number)	void
updateLostOfferReason	updateLostOfferReason(Id: number, lostDetails: LostReasonModel)	void

Method	Signature	Returns
unLostSingleOffer	unLostSingleOffer(id: number)	void
deleteSingleOffer	deleteSingleOffer(id: number)	void
getContractualCommissionByPrincipalId	getContractualCommissionByPrincipalId(id: number)	void
extendSingleOfferValidatiy	extendSingleOfferValidatiy(offer: SalesOffers)	void
convertJobToOrder	convertJobToOrder(id: number)	void

Properties

Property	Type
datasourceBySearchEnum	any

Where it refuses work

- `NewJobService` stops the work with an early return when `url !== ""`.

Diagram

```
graph LR
  SalesScreen[Sales New-Job Screen] --> Service[NewJobService]
  Service --> Branch[getCurrentBranch]
  Service --> SalesResponsibles[getSalesResponsiblesDataSource]
  Service --> SalesResponsiblesEnum[getSalesResponsiblesDataSourceWithEnum]
  Service --> ProductTypes[getProductTypesDataSource]
  Service --> PurchasingTypes[getPurchasingProductTypesDataSource]
  Service --> TimeFrames[getTimeFramePeriodsDataSource]
  Service --> Statuses[getStatusDataSource]
  Service --> Save[saveJob]
  Service --> Update[updateJob]
  Service --> Delete[deleteInquiry]
```

Usage

```
export class NewJobComponent {
  constructor(private readonly newJobService: NewJobService) {}

  loadFormData() {
    const branch = this.newJobService.getCurrentBranch();
    const salesResponsibles = this.newJobService.getSalesResponsiblesDataSource();
    const productTypes = this.newJobService.getProductTypesDataSource();
    const timeFrames = this.newJobService.getTimeFramePeriodsDataSource();
    const statuses = this.newJobService.getStatusDataSource();

    return {
      branch,
      salesResponsibles,
      productTypes,
    };
  }
}
```

```

        timeFrames,
        statuses,
    };
}

save() {
    return this.newJobService.saveJob();
}

update() {
    return this.newJobService.updateJob();
}

removeInquiry() {
    return this.newJobService.deleteInquiry();
}
}

```

AI Coding Instructions

- Use `NewJobService` as the integration point for new-job form data and job-related actions.
- Select the sales responsible source that matches the consuming control: use `getSalesResponsiblesDataSourceWithEnum()` only where enum-backed values are expected.
- Keep branch, product type, purchasing product type, time-frame, and status loading in the screen or state layer; avoid duplicating those sources locally.
- Route save, update, and inquiry deletion through `saveJob()`, `updateJob()`, and `deleteInquiry()` rather than adding direct request logic in UI components.

Used by

6 references from 6 files. Each is a place in this repository where the symbol is actually used — go read one rather than trusting an example.

Imported by (6)

- `ReportsSettingsComponent` — `Pams/Web/Pams.Web/Client/app/components/configuration/reports-settings/reports-settings/reports-settings.component.ts :1`
- `TopicComponent` — `Pams/Web/Pams.Web/Client/app/components/dashboard/my-desk/activities/topic/topic.component.ts :1`
- `InvoiceDetailsComponent` — `Pams/Web/Pams.Web/Client/app/components/invoices/invoice-details/invoice-details.component.ts :1`
- `SampleSelectBoxComponent` — `Pams/Web/Pams.Web/Client/app/components/shared/dropdown/sample-select-box/sample-select-box.component.ts :1`
- `TagComponent` — `Pams/Web/Pams.Web/Client/app/components/shared/tag/tag.component.ts :1`
- `PamsServicesModule` — `Pams/Web/Pams.Web/Client/app/services/pams-services.module.ts :1`