



PAMS

CityController

Kind: Controller

VERSION
4

UPDATED
11 August 2026

DOCUMENT
reference-subsystem-pams/controller-citycontroller

CONTENTS

1	Where it refuses work	2	3	Relationships	2
2	When something fails	2	4	Used by	7

Kind: Controller

Source: `Pams/API/Pams.API/Controllers/Common/CityController.cs` (line 20)

Part of: [Pams](#)

1 Where it refuses work

- `CityController` stops the work with an early return when `!success`, in 3 places.
- `CityController` stops the work with an early return when `!ms.HasObject`, in 2 places.
- `CityController` stops the work with an early return when `!ModelState.IsValid`, in 2 places.
- `CityController` stops the work with an early return when `ms.HasObject`.

2 When something fails

- `CityController` handles failure in 6 places: it turns it into a return value in all 6.

3 Relationships

- MODULE_DECLARES → `GetAll`
- MODULE_DECLARES → `GetByID`
- MODULE_DECLARES → `Insert`
- MODULE_DECLARES → `Update`
- MODULE_DECLARES → `Save`
- MODULE_DECLARES → `Delete`
- IMPORTS → `City`
- IMPORTS → `BaseController`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`

- [illegible]

- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Save
- IMPORTS → Save
- IMPORTS → Save
- IMPORTS → Save
- IMPORTS → Save
- IMPORTS → Save

-
- IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Save](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
 - IMPORTS → [Update](#)
-

- [illegible]

- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete

4 Used by

3 references from 3 files. Each is a place in this repository where the symbol is actually used — go read one rather than trusting an example.

calls by (3)

- AppSettings — Frontend/src/app/settings/app/app.settings.ts :241
- AppSettings — Pams/Web/Pams.Web/Client/app/settings/app/app.settings.ts :126
- AppSettings — Pams/Web/Pams.WebApp/Client/app/settings/app/app.settings.ts :6