

CustomFieldController

August 18, 2026

CustomFieldController

Kind: Controller

Source: Pams/API/Pams.API/Controllers/CustomField/CustomFieldController.cs (line 15)

Part of: [Pams](#)

Where it refuses work

- CustomFieldController stops the work with an early return when `isSaved` , in 2 places.
- CustomFieldController stops the work with an early return when `model.CustomFields == null || model.CustomFields.Count == 0` .
- CustomFieldController stops the work with an early return when `list.Any(a => a.Id == 0)` .
- CustomFieldController stops the work with an early return when `!isCreated` .
- CustomFieldController stops the work with an early return when `!isRemoved` .
- CustomFieldController stops the work with an early return when `isRenamed` .

Relationships

- MODULE_DECLARES → `GetLookupFieldTypes`
- MODULE_DECLARES → `GetLookupAppModules`
- MODULE_DECLARES → `GetLookupAppProperties`
- MODULE_DECLARES → `GetLookupAppSubModules`
- MODULE_DECLARES → `GetCustomFieldsOfModelById`
- MODULE_DECLARES → `GetCustomFieldsOfObjectById`
- MODULE_DECLARES → `GetCustomFieldsWithValuesOfObjectById`
- MODULE_DECLARES → `CreateCustomFieldList`
- MODULE_DECLARES → `RemoveCustomField`

- MODULE_DECLARES → RenameCustomField
- MODULE_DECLARES → SetCustomField
- MODULE_DECLARES → DeleteCustomFieldValue
- IMPORTS → BaseController
- IMPORTS → Module
- IMPORTS → ModuleBindingModel
- IMPORTS → PageFieldBindingModel
- IMPORTS → CreateCustomFieldModel
- IMPORTS → CompanyCustomFieldModel

Used by

2 references from 2 files. Each is a place in this repository where the symbol is actually used — go read one rather than trusting an example.

calls by (2)

- AppSettings — Frontend/src/app/settings/app/app.settings.ts :241
- AppSettings — Pams/Web/Pams.Web/Client/app/settings/app/app.settings.ts :126