



PAMS

MaritalStatusController

Kind: Controller

VERSION
4

UPDATED
11 August 2026

DOCUMENT
reference-subsystem-pams/controller-maritalstatuscontroller

CONTENTS

1	Where it refuses work	2	3	Relationships	2
2	When something fails	2	4	Used by	6

Kind: Controller

Source: `Pams/API/Pams.API/Controllers/Common/MaritalStatusController.cs` (line 16)

Part of: [Pams](#)

1 Where it refuses work

- `MaritalStatusController` stops the work with an early return when `!success`, in 3 places.
- `MaritalStatusController` stops the work with an early return when `!ms.HasObject`, in 2 places.
- `MaritalStatusController` stops the work with an early return when `c.Exists(0, model.Name)`.
- `MaritalStatusController` stops the work with an early return when `c.Exists(model.MaritalStatusID, model.Name)`.

2 When something fails

- `MaritalStatusController` handles failure in 6 places: it turns it into a return value in all 6.

3 Relationships

- MODULE_DECLARES → `GetAll`
- MODULE_DECLARES → `GetByID`
- MODULE_DECLARES → `Insert`
- MODULE_DECLARES → `Update`
- MODULE_DECLARES → `Save`
- MODULE_DECLARES → `Delete`
- IMPORTS → `BaseController`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`
- IMPORTS → `GetAll`

- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → MaritalStatus
- IMPORTS → GetByID
- IMPORTS → GetByID
- IMPORTS → GetByID
- IMPORTS → GetByID

- [illegible]

- [illegible]

4 Used by

6 references from 6 files. Each is a place in this repository where the symbol is actually used — go read one rather than trusting an example.

calls by (6)

- `EmployeeService` — `Frontend/src/app/services/person/employee.service.ts` :1
- `EmployeeService` — `Pams/Web/Pams.Web/Client/app/services/person/employee.service.ts` :1
- `EmployeeService` — `Pams/Web/Pams.WebApp/Client/app/services/person/employee.service.ts` :1
- `AppSettings` — `Frontend/src/app/settings/app/app.settings.ts` :241
- `AppSettings` — `Pams/Web/Pams.Web/Client/app/settings/app/app.settings.ts` :126
- `AppSettings` — `Pams/Web/Pams.WebApp/Client/app/settings/app/app.settings.ts` :6