

ReactivationReasonsController

August 19, 2026

ReactivationReasonsController

Kind: Controller

Source: Pams/API/Pams.API/Controllers/Common/ReactivationReasonsController.cs (line 15)

Part of: Pams

Where it refuses work

- `ReactivationReasonsController` stops the work with an early return when `ModelState.IsValid` , in 4 places.
- `ReactivationReasonsController` stops the work with an early return when `!success` , in 3 places.
- `ReactivationReasonsController` stops the work with an early return when `!ms.HasObject` , in 2 places.
- `ReactivationReasonsController` stops the work with an early return when `ms.HasObject` .
- `ReactivationReasonsController` stops the work with an early return when `c.Exists(model.ReactivationReasonID, model.Name)` .

When something fails

- `ReactivationReasonsController` handles failure in 6 places: it turns it into a return value in all 6.

Relationships

- MODULE_DECLARES → `GetAll`
- MODULE_DECLARES → `GetByID`
- MODULE_DECLARES → `Insert`
- MODULE_DECLARES → `Update`

- MODULE_DECLARES → Save
- MODULE_DECLARES → Delete
- IMPORTS → ReactivationReasons
- IMPORTS → BaseController
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetAll
- IMPORTS → GetByID
- IMPORTS → GetByID
- IMPORTS → GetByID
- IMPORTS → GetByID
- IMPORTS → GetByID

- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → GetById
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert
- IMPORTS → Insert

- [illegible]

- IMPORTS → Save
- IMPORTS → Save
- IMPORTS → Save
- IMPORTS → Save
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Update
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete

- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete
- IMPORTS → Delete

Used by

3 references from 3 files. Each is a place in this repository where the symbol is actually used — go read one rather than trusting an example.

calls by (3)

- AppSettings — Frontend/src/app/settings/app/app.settings.ts :241
- AppSettings — Pams/Web/Pams.Web/Client/app/settings/app/app.settings.ts :126
- AppSettings — Pams/Web/Pams.WebApp/Client/app/settings/app/app.settings.ts :6